

## MTL GECMA RT

### Remote Terminal for hazardous areas - zone 1/2 (gas)

- **Platform, modular design concept**
- **Lightweight, slimline design**
- **Specified for use in hazardous areas with Ex approvals**
- **Display options 19", 22" or 24", in different resolutions**
- **Fibre optic or copper data transmission**
- **Designed for maximum performance and reliability in harsh environments**
- **DVI & USB interfaces**
- **Savings of software licence costs**
- **Unique intrinsically safe and alarm visualisation**



**As part of the MTL GECMA Work Station (WS) range, the MTL GECMA Remote Terminal (RT) is an operating terminal designed to enhance visualization within your process using high resolution display options of 19", 22" or 24".** They can be specified for use as a Remote Terminal within the strictest of hygienic conditions, aggressive indoor and outdoor production environments and in Ex areas typically found in pharmaceutical, chemical, petro chemical, oil & gas and off-shore manufacturing.

**This latest generation of MTL GECMA Remote Terminals from Eaton allows digital data communications** to a localised terminal via copper or fibre optic cable, giving you seamless transmissions over significantly longer distances if required. The video system will scale many video input modes into the native format of the LCD panel whilst preserving the aspect ratio of the source image, offering the best image quality.

**MTL GECMA RT displays are of the highest industrial quality.** To ensure the best readability the terminal incorporates optical bonding and LED-backlit technology resulting in a high resolution image in a low power display.

**The MTL GECMA RT has been designed to conform to a wide range of international Ex-approvals.** International companies can operate using the same system, setup and interfaces worldwide, increasing overall safety, reliability and highest dependability across their business, whilst offering easy installation, individual design and consistency with a 'state-of-the-art' solution.

**Its slim, flexible modular construction** can be used in even the harshest environments and allows the MTL GECMA RT to be specified to meet your plant's requirements with the added benefit of a quality product. This not only shortens delivery time considerably but with maintenance now possible by changing modules, even on site, increases your plants availability.

**MTL GECMA RT is also available with a large range of specialised housing options,** the modular design concept enables you to benefit from a cost effective, tailored and customised solution for your application installation.

**The multiple interfaces** future-proof your investment and allows easy expansion for additional connected devices, such as scanners or printers.

**Existing MTL GECMA remote operating systems can be upgraded quickly and easily** without installing new cables, resulting in state-of-the-art visualisation technology utilising existing cables (applicable to copper versions only).\*

*\*Contact us for more details*

**EATON**  
Powering Business Worldwide

**Eaton Electric Limited,**  
Great Marlings, Butterfield, Luton  
Beds, LU2 8DL, UK.  
Tel: + 44 (0)1582 723633 Fax: + 44 (0)1582 422283  
E-mail: [mtlenquiry@eaton.com](mailto:mtlenquiry@eaton.com)  
[www.mtl-inst.com](http://www.mtl-inst.com)

© 2017 Eaton  
All Rights Reserved  
Publication No. EPS MTL GECMA RT Rev 1 210217  
February 2017

## SPECIFICATION

## ELECTRICAL

	19"	22"	24"
<b>Screen size:</b>	19 inch (48 cm) - across diagonal	21.5 inch (54 cm) - across diagonal	24 inch (61 cm) - across diagonal
<b>Screen type:</b>	LCD thin film technology (TFT) with LED backlight		
<b>Display:</b>	1280 x 1024 pixels, lower resolutions are interpolated, 5:4 picture format, 16.7 million colours	1920 x 1080 pixels, lower resolutions are interpolated, 16:9 picture format, 16.7 million colours	1920 x 1200 pixels, lower resolutions are interpolated, 16:10 picture format, 16.7 million colours
<b>Brightness:</b>	250 cd/m <sup>2</sup>		
<b>Contrast ratio:</b>	1000:1 typical		
<b>Viewing angle:</b>	170/160° typical at CR ≥ 10		
<b>Touch screen (optional):</b>	Resistive 5-wire glass touch screen		
<b>Technology:</b>	Proprietary full digital KVM transmission		

## TERMINAL UNIT

<b>Power supply:</b>	AC 100-240V AC, 50/60Hz, DC 20-30V DC
<b>Input power:</b>	50W (typical) 100W (maximum)
<b>Pointing Devices:</b>	2x Ex i PS/2 for keyboard and pointing device
<b>Universal port:</b>	4 x USB 2.0 intrinsically safe, transparent USB
<b>Serial port:</b>	RS232
<b>Data cable (copper):</b>	CAT 6A or higher recommended*
<b>Fibre-optic cable:</b>	Multi mode or Single mode

## MECHANICAL

<b>Housing material:</b>	Stainless steel V2A, EN std 1.4301, SAE grade 304 V4A, EN std 1.4404, SAE grade 316L (optional) Electro polishing (optional)		
<b>Weight:</b>	65kg (full terminal)	69kg (full terminal)	75kg (full terminal)
<b>Dimensions (mm):</b>	(W x H x D) 509 x 429 x 50	(W x H x D) 610 x 400 x 50	(W x H x D) 675 x 461 x 50
<b>Module assembly dimension without housing (mm):</b>	509 (W) x 429 (H) x 125 (D*) *depth behind mounted display module	610 (W) x 400 (H) x 125 (D*) *depth behind mounted display module	675 (W) x 461 (H) x 125 (D*) *depth behind mounted display module

## SAFE AREA UNIT

<b>Power supply:</b>	100 - 240VAC 50/60Hz
<b>Input power:</b>	6W (typical) 25W (maximum) @ 4-fold Rack
<b>Data and KB/Mouse port:</b>	USB
<b>Serial port:</b>	RS232
<b>Video In:</b>	DVI-D (DVI-I / VGA on request)
<b>Video out:</b>	DVI-D

## ENVIRONMENTAL


<b>Temperature:</b>	Operating ambient temperature: -10°C to +50°C (10-90% RH, non-condensing) Certified ambient temperature: -30°C to +60°C (10-90% RH, non-condensing) Ambient storage temperature: -40°C to +70°C (10-90% RH, non-condensing)
<b>Ingress protection:</b>	IP66 (front side)

\*Contact us for more details


CERTIFICATION

Authority:	Certificate Com Module: IECEx: SIR 14.0031X ATEX: 14ATEX5062X
Approved for:	Certification Com Module: With op is interface Ex mb[ib] op is IIC T4 Gb. Without op is interface Ex mb[ib] IIC T4 Gb.

OPERATING PRINCIPLE



ENCLOSURE OPTIONS



Further enclosure options on request

\*Please contact your local sales office for these options



**Eaton Electric Limited,**  
Great Marlings, Butterfield, Luton  
Beds, LU2 8DL, UK.  
Tel: + 44 (0)1582 723633 Fax: + 44 (0)1582 422283  
E-mail: [mtlenquiry@eaton.com](mailto:mtlenquiry@eaton.com)  
[www.mtl-inst.com](http://www.mtl-inst.com)

© 2017 Eaton  
All Rights Reserved  
Publication No. EPS MTL GECMA RT Rev 1 210217  
February 2017

**EUROPE (EMEA):**  
+44 (0)1582 723633  
[mtlenquiry@eaton.com](mailto:mtlenquiry@eaton.com)

**THE AMERICAS:**  
+1 800 835 7075  
[mtl-us-info@eaton.com](mailto:mtl-us-info@eaton.com)

**ASIA-PACIFIC:**  
+65 6645 9864 / 9865  
[sales.mtlsing@eaton.com](mailto:sales.mtlsing@eaton.com)

The given data is only intended as a product description and should not be regarded as a legal warranty of properties or guarantee. In the interest of further technical developments, we reserve the right to make design changes.