

# GECMA RT safe area unit

# Desktop version fibre optic

The GECMA RT safe area unit is a single video channel transmission unit. It enables the transparent Keyboard-Video-Mouse (KVM) transmission via Multi Mode or Single Mode Fibre cable from the safe area into the hazardous area through an intrinsically safe, digital data transmission. A distance of up to 10.000m can be reached at a resolution of up to 1920x1200 pixel depending on the version of the safe area unit.



#### **Features**

Digital Video In DVI-D (Digital only-VGA on request)

Digital Video Out DVI-D (Digital only)

USB In Transparent USB 2.0 connection for keyboard and pointing device

RS232 Single Channel RS232 connection

**FIBRE LINK** 

Multi Mode Single Mode

 Category
 OM3
 OS2

 Wave length
 850nm
 1310nm

 Optical Budget
 7,3dBm
 12,8dBm

**Distance** up to  $550 \text{m} (50/125 \mu \text{m})$  up to  $10.000 \text{m} (9/125 \mu \text{m})$ 

Resolution up to 1920 x 1200 pixel, Full HD 1080p resolution at 1920x1080 @ 60Hz and 16:9 picture format

Technical data sheets are subject to modifications and amendments / No liability for misprints and errors.



Eaton Electric Limited,

Great Marlings, Butterfield, Luton Beds, LU2 8DL, UK. Tel: + 44 (0)1582 723633 Fax: + 44 (0)1582 422283 E-mail: mtlenquiry@eaton.com www.mtl-inst.com

© 2016 Eaton All Rights Reserved Publication No. EPS GECMA RT SAU DT rev 2 September 2016

#### **Features**

Designation GECMA RT safe area unit /desktop

Housing Desktop housing

**Power Supply** 100 - 240 V AC / 50/60 Hz /, typical: 10W maximum:  $48\,W$ 

**Power Input** 6 W

DVI/VGA IN, DVI OUT, RS232 IN, USB IN, FIBRE LINK Connections

**Fuses** 


**Dimensions** 203mm Width x 52mm Height x 191mm Depth


Weight 1.6 kg

**Certified Ambient Temperature** -30 °C ≤Ta ≤ +60 °C **Operating Ambient Temperature** -10 °C ≤Ta ≤ +50 °C

# **Article Codes**


GEC-GE1RT-TSM01-00 GECMA RT Safe Area Unit Desktop Version MM (Multi Mode) GEC-GE1RT-TSS01-00 GECMA RT Safe Area Unit Desktop Version SM (Single Mode)







# Standard Setup with DVI/ USB Connection





# Eaton Electric Limited,

Great Marlings, Butterfield, Luton Beds, LU2 8DL, UK. Tel: + 44 (0)1582 723633 Fax: + 44 (0)1582 422283

E-mail: mtlenquiry@eaton.com

www.mtl-inst.com

© 2016 Eaton All Rights Reserved

Publication No. EPS GECMA RT SAU DT rev 2 210916 September 2016

# EUROPE (EMEA):

+44 (0)1582 723633 mtlenquiry@eaton.com

# THE AMERICAS:

+1 800 835 7075 mtl-us-info@eaton.com

# ASIA-PACIFIC:

+65 6 645 9888

sales.mtlsing@eaton.com

The given data is only intended as a product description and should not be regarded as a legal warranty of properties or guarantee. In the interest of further technical developments, we reserve the right to make design changes.